




Superior StreetSiren DoubleDeck Fibra

Wired siren with a clip lock for a branded faceplate.
For outdoor and indoor use.



Ajax Superior products are available exclusively to accredited Ajax Systems partners for sales, installation, and maintenance, creating a protected, high-value revenue channel.



Additional promotion of security services


A standout feature of Superior StreetSiren DoubleDeck Fibra is the Brandplate faceplate that gives security service providers the option to print their logo and contact information directly on the siren's front panel.

This allows the siren to serve as an additional marketing channel, helping reach new customers by catching the attention of neighbors and passersby.




One device, five missions

- The alarm scares off intruders and attracts attention
- Security status indication notifies users when the system is being armed/disarmed and during entry/exit delays
- The siren's LED frame lights up to indicate system arming or security mode change
- The Chime feature informs users if opening detectors are triggered while the system is disarmed
- After-alarm LED indication alerts users and passing patrols to any alarms in the system



Adjustable alarm alerts

- Group mode enables the siren to respond only to alarms and security mode changes in its assigned group
- Adjustable volume¹ of alarm and notifications: from 85 dB to 113 dB
- Adjustable alarm duration: from 3 seconds to 3 minutes
- No limit on the number of sirens in a single system²



Fibra


communication technology

- Up to 2,000 m (6,550 ft) of wired communication
- Data is encrypted throughout the transmission process
- Regular polling to display current device states
- One line for different types of devices
- Automatic firmware updates³




Enhanced power management

- Pre-installed rechargeable battery for additional power supply during alarms
- Power supply calculator
- Power consumption stress test



Sabotage resistance


- Tamper⁴ alarm
- Protection against short circuits
- Device authentication to prevent spoofing
- Durable enclosure



Quick installation

- Pairing with the system via a QR code or line scanning
- SmartBracket mounting panel for installation without disassembling the enclosure
- Bubble level to check the inclination angle of the mounting during installation
- Remote control and configuration in Ajax apps

Brandplate is available in sets of 10 pieces and is sold separately from StreetSiren DoubleDeck Fibra. The panel comes in both black and white. When ordering 4 Brandplate sets (40 panels) or more, you get a complimentary print of a single design on all of them.

Compliance with standards EN 50131 (Grade 3) PD 6662:2017 INCERT SSF Compatibility with hubs  For detailed information, scan the QR code or follow the link: ajax.systems/tools/devices-compatibility/?models=SS.DD.F	Alerts Alarms Acoustic LED Entry/exit delays Acoustic Security mode change Acoustic LED Security status LED Chime Acoustic If enabled, the siren makes a short beep to indicate that the opening detectors are triggered when the system is disarmed. After-alarm indication LED	Communication with a hub Fibra communication technology Wired connection U/UTP cat.5 4×2×0.51 mm (24 AWG) cable, copper conductor 4×0.22 mm² signal cable, copper conductor Communication range up to 2,000 m up to 6,550 ft With U/UTP cat.5 4×2×0.51 mm (24 AWG) cable	Features Types of alerts Acoustic LED Alarm volume from 85 dB to 113 dB at a distance of 1 m (3.3 ft) Adjusted by a PRO or a user with admin rights in Ajax apps Alarm duration from 3 s to 3 min Adjusted by a PRO or user with admin rights via Ajax apps Piezoelectric buzzer frequency 3.5 ± 0.5 kHz
Power supply Main power supply 7–26 V⁼⁼, up to 1130 mW The device is powered by the hub or Superior LineSupply Fibra Backup LTO 18650, 1500 mAh, 2.4 V⁼⁼ Up to 30 min of alarm signaling after main power failure	Installation Operating temperature –25 °C to +60 °C –13 °F to 140 °F Operating humidity up to 95% Protection class IP54 Recommended installation height 2.5 m or higher 8 ft or higher	Enclosure Color black, white Dimensions 199 × 199 × 60 mm 7.83" × 7.83" × 2.6" Weight For device in black 522 g 18.4 oz For device in white 531g 18.7 oz Tamper alarm	Complete set Superior StreetSiren DoubleDeck Fibra SmartBracket mounting panel Installation kit Quick start guide

¹ Measured at a distance of 1 m (3.3 ft).
² Available for sirens with firmware version 8.64.1.0 or later. The siren must be added to a hub running OS Malevich 2.36 or later.
³ Automatic firmware updates are available for sirens with firmware version 8.64.1.0 or later. The siren must be added to a hub running OS Malevich 2.36 or later.
⁴ Any attempt to open the enclosure triggers a tamper alarm.



For detailed information, scan the QR code or follow the link:
ajax.systems/support/devices/superior-streetsiren-doubleddeck-fibra/